

OPC-3301i

CCD Linear Imager

The OPC-3301i features a high speed, CCD barcode scanner and a lightweight, ergonomic design that is perfect for all day, everyday use in a wide variety of applications. The cordless, cable-free freedom of Bluetooth® wireless communication offers the ability to roam away from the host device, which improves productivity and scanning convenience.



Highlights

- Wireless CCD barcode scanner with enhanced decoding algorithms for ultra-fast (300 scans/second) barcode scanning
- Reads 1D barcodes from LCD screens and mobile phones and capable of scanning negative barcodes (white bars on black spaces)
- Supports Apple MFi, SPP and HID Bluetooth profiles for added flexibility
- Memory: 1MB SDRAM, 1MB Flash ROM
- Small form factor: 113 x 132 x 56 mm (WxHxD) and 127 grams including battery
- Extremely durable: IP42 rating against dust and moisture and survives 1.5 m drop to concrete
- Sold separately: CHG-3201 charging cradle, CRD-3301B charging/communication cradle and OPA-3201 Bluetooth dongle
- Backed by a two year warranty

OPC-3301i

Product Specifications



Memory

CPU: 32-bit
Flashrom: 1 MB
RAM: 96 Kbyte

Operating indicators

Visual: 2 LED, 1 (red/green), 1 (blue)
Non-visual: buzzer

Operating keys

Entry options: 1 scan key

Communication

Bluetooth: Ver. 2.1, SPP/HID, output power class 2, range up to 10 m, 1 to 1 connection, master / slave mode, authentication and encryption

Power

Current consumption: 15 mA (standby), max 200 mA
Battery: Lithium-Ion 3.7V 1100 mAh
Standby time: Approx. 72 hours (with wireless connection)
Reading: Approx. 48 hours (1 scans / 5 seconds)
Charging method: Separate cradle CHG-3201 / CRD-3301B
Battery charging time: Ca. 3 hours (when charged with power supply)

Barcode scanner optics

Light source: 624 nm LED
Scan method: CCD linear image sensor
Scan rate: 300 scans / second
Trigger mode: manual, auto-trigger
Reading pitch angle: $\pm 50^\circ$
Reading skew angle: $\pm 65^\circ$
Reading tilt angle: $\pm 25^\circ$
Curvature: R>15 (EAN 8), R>20 (EAN 13)
Min. resolution at PCS 0.9: 0.1 mm / 3.94 mil
Min. pcs value: 0.30
Depth of field at code 39:
55 - 75 mm (0.127 mm) / 2.17 - 2.95 in (5 mil)
45 - 100 mm (0.15 mm) / 1.77 - 3.94 in (6 mil)
35 - 175 mm (0.25 mm) / 1.38 - 6.89 in (10 mil)
40 - 300 mm (0.5 mm) / 1.57 - 11.81 in (20 mil)
60 - 500 mm (1.0 mm) / 2.36 - 19.69 in (40 mil)

Supported symbologies

Barcode (1D): JAN/UPC/EAN incl. add on, Codabar / NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Matrix 2of5, MSI/Plessey, UK/Plessey, S-Code, Telepen, Tri-Optic
Postal code: Chinese Post, Korean Postal Authority code

Durability

Temperature in operation: 0 to 50 °C / 32 to 122 °F
Temperature in storage: -20 to 60 °C / -4 to 140 °F
Humidity in operation: 20% to 85% (non-condensing)
Humidity in storage: 20% to 85% (non-condensing)
Ambient light immunity: Incandescent 10,000 lx max, Fluorescent 10,000 lx max, direct sun 100,000 lx max
Drop test: 1.5 m / 5 ft drop onto concrete surface
Vibration test: 10 - 100 Hz with 2G for 1 hour
Protection rate: IP42

Physical

Dimensions (W x H x D): 113 x 132 x 56 mm / 4.45 x 5.20 x 2.20 in.
Weight body: Ca. 127 g / 4.3 oz (incl. battery)
Case: ABS, Black or White

Regulatory & safety

Product compliance: CE, UKCA, FCC, VCCI, MFi, RoHS, REACH

Items

Enclosed: Wrist strap
Sold separately: CHG-3201 cradle (charging), OPA-3201 (Bluetooth HID-dongle), CRD-3301B cradle (charging and communication)